

SOLID 52A4

**HIGHEST
PERFORMANCE FOR
LOGISTICS, AUTOMOTIVE
AND INTEGRATION**

A4 Laser Printer for Just-in-Time Applications

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- WIFI and PDF direct printing optional
- Duplex printing standard
- Flexible extension options for paper feed and tray
- Full integration in production lines through GPIO / Status-Out

FIELD OF APPLICATION

- Paper exit face-up and face-down
- Integration with GPIO bi-directional communication
- Special paper sizes like A6, small GTL (74 x 210 mm)
- Printing with different emulations (PCL5, IGP, IPDS, etc.)



Print Engine

Print technology	Laser, OPC heat / pressure
Controller	MPC 7.1
Print speed	up to 52 pages/minute (A4) first page: approx. 5,9 s
Print resolution	max. 600 dpi x 600 dpi
Duty cycle	up to 50.000 pages (A4) (based on a using period of 60 months) max. 250.000 pages (A4)
Power supply	220-240 VAC, 50/60 Hz
Power consumption	700 W (Sleep Mode: 4,2 W)
Dimensions (WxDxH in mm)	428 x 511 x 442
Weight	26 kg (incl. consumables)
Noise	< 57 dB (A)
Environment temperature	10 - 32°C
Relative humidity	8 - 80 % (rel., non condensing)
Interfaces	USB 2.0, Ethernet-Interface, 10/100 MBit, bi-directional (TCP/IP)
Factory Option	IEEE 1284 (Centronics)
Option	RS232, RS422 WiFi: IEEE 802.11 n/g/b, WEP with 64 and 128 Bit, WPA/WPA2, WPA-PSK/WPA2-PSK
Memory	RAM: 1024MB Flash: 32 GB

MPC 7.1 High-End Print-Controller

Emulations

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno, μ -Postscript, LN03+, BULL-MP6090, Datamax, Etimark MP-1220, TEC Bx72, TEC B6xx, LDC, ZPLII, EPL 2, Intermec Direct Protocol, IER Command, cab, Godex EZPL, Diablo 630, IBM Proprinter, EPSON FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, HP Designjet, XML (SAP® RFID), CUPS Raster

Optional Emulations

CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP/PGL, Labelpoint, IPDS, AEA, PDF Direct Printing*, (more emulations on request)

Barcodes

Codabar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic), Interleaved 2/5 (3-Stroke Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

Optional Barcodes (Barcode 2)

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5, (more barcodes on request)

Additional functions

Network capabilities	authentication standard IEEE 802.1X
Intelligent barcode generation	on-the-fly in the printer
Format splitting	in several subformats by command
Integrated form management (RFM)	Forms and fonts can be stored in the flash memory and can be accessed when needed

Optional functions

Status-Out

Gives notice of each correctly printed page via interface. Further features can be found in the manual.

Programmable GPIO-Interface (SPS-Control)

EMBEDDED INTELLIGENCE – Enabling two-way communication between printer and a PLC.

Integration of the printer into production lines is possible, controlled by GPIO-interface

Customer / Application specific modifications possible. Further features can be found in the manual.



Printable Media

Size	A6 to A4, special formats on request
Weight	60 - 203 g/m ² Duplex 60 - 203 g/m ²

Paper Path

Input (Standard)

Cassette 1: 550 sheets (Ax to A4) 75 g/m²

Output (Standard)

550 sheets (75 g/m²)

Input (optional)

550 sheets (75 g/m²) tray
550 sheets (75 g/m²) lockable tray

up to 4 x 550 sheet trays usable

or 3 x 550 sheet trays
plus 1 x 2100 sheet tray (75 g/m²)
Caster Base for 2100 sheet tray needed

Output (optional)

Output expander 500 sheets (75 g/m²) (upt to 3 times)
Face-up-Option

Other options

Spacer (non functioning input tray to elevate the printer)

Caster Base (only necessary for 2100 sheet tray)

SOLID 52A4 MICR as extra model available.

* Only available with MPC 3.4, MPC 7.1 and MPC 8.x

The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 22.08.2022

EMEA
APAC

MICROPLEX PRINTWARE AG
Panzerstraße 5, 26316 Varel
Germany
Phone: +49 4451 91370
E-Mail: sales@microplex.de

AMER
Canada

MICROPLEX PRINTWARE CORPORATION
30300 Solon Industrial Pkwy Suite E, Solon, OH 44139
USA
Phone: +1 440-374-2424
E-Mail: info@microplex-usa.com

